

CERTIFICATE OF COMPLIANCE

Certificate Number E363518
Report Reference E363518-20200529
Issue Date 2020-SEPTEMBER-30

Issued to: LUMIRON INC
20725 Ne 16Th Ave Ste A33
Miami, FL 33179-2126 United States

**This certificate confirms that
representative samples of**

LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS,
LUMINAIRES AND FITTINGS

See Addendum Page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

See Addendum Page for Standards

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E363518
Report Reference E363518-20200529
Issue Date 2020-SEPTEMBER-30

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standards for Safety:

UL 2108, Low Voltage Lighting Systems.
CSA C22.2 No. 250.0-08, Luminaires
UL 8750, Light Emitting Diode (LED) Light Sources for Use in Lighting Products

LED low-voltage luminaires, surface, class 2 luminaires, "Dakota Series":

Model(s) LUMIR-LLPF-XX-YY-Z-V-C [a][c], LUMIR-LLPR-XX-YY-Z-V-C [b][c], LUMIR-LLBX-XX-YY-Z-V-C [c]

- [a] - Where "(F)" and "F", represent employing the flexible Printed Wiring Board.
- [b] - Where "(R)" and "R" represent employing rigid Printed Wiring Board.
- [c] - Where "XX" represents width of the LED panel, "YY" represents length of the LED panel, "Z" represents the direction of light source, "V" represents input DC voltage, "C" represents input current.

Standards for Safety:

UL 2108, Low Voltage Lighting Systems
CSA C22.2 No. 250.0-08, Luminaires

LED low-voltage luminaires, surface, class 2 luminaires, "Dakota Series":

Model(s) LUMIR-FPC-XX-YYY-X-12 [d], LUMIR-FPC-XX-YYY-X-24 [d], LUMIR-FR4-XX-YYY-X-12 [d], LUMIR-FR4-XX-YYY-X-24 [d]

- [d] - Where "XX" can be any letter between A-Z or any number between 0-9 to represent color temperature, "YYY" represents the quantity of LED per meter, and the last "X" represents the wattage per meter.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

